



S-TRONIC

Hightec-HC-Synthetic-Motor Oil 5W40

Description:

S-TRONIC is a high-tech, HC synthetic engine oil which has been developed for petrol and diesel car engines, and is ideal for modern uprated fuel injection and turbo engines.

S-TRONIC meets the high quality requirements of the car manufacturers. It is excellently applicable for long oil change intervals.

Ideal for hard use at motorways and over short distances.

Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxydation- and thermo stability

Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Lowest oil consumption
- High margin of performance and high product stability
- Extended oil change intervals
- Prevents black sludge formation
- All-year operation

Suitable for/ we recommend this product for

| | |
|--------------------------------|--------------------|
| SAE | 5W-40 |
| API | SN/CF/EC |
| ACEA | A3/B4 |
| We recommend this product for: | |
| BMW | Longlife-01 |
| FIAT | 9.55535-M2, H2, N2 |
| MB-Approval | 229.3 |
| OPEL | GM-LL-B-025 |
| PORSCHE | A40 |
| PSA | B71 2296 |
| RENAULT | RN0700/0710 |
| VW | 502.00, 505.00 |

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal:

- **S-TRONIC** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **S-TRONIC** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **S-TRONIC** it is recommendable to use only **S-TRONIC** when refilling.

S-TRONIC

| Article No. | Packaging unit | |
|-------------|----------------|--------|
| 300622 | Can | 1 L |
| 300623 | Can | 4 L |
| 300624 | Can | 5 L |
| 300625 | Can | 20 L |
| 300626 | Drum | 60 L |
| 300628 | Drum | 200 L |
| 340629 | PE-Container | 1000 L |

Typical characteristics:

| | | |
|----------------------------|--------------------|------|
| Specific weight at 15°C | kg/m ³ | 854 |
| Dynamic viscosity at -30°C | mPa.s | 6060 |
| Viscosity at 40°C | mm ² /s | - |
| Viscosity at 100°C | mm ² /s | 14,7 |
| Viscosity index | | 173 |
| Flash point COC | °C | 226 |
| Pourpoint | °C | -42 |
| Sulphate ashes | % | - |
| TBN | mgKOH/g | 10,5 |

Data are subject to change.

Attention: Service instructions should be observed!

KL/MO/PKW/-/-
08/2021