



TRONICSTAR C2

Fuel-Economy Mid SAPS-HC-Synthetic-Motor Oil 5W30

Description:

TRONICSTAR C2 is a further developed Fuel Economy (FE) HC- synthetic fuel-efficient engine oil with the viscosity SAE 5W-30. The exceptional qualities of this high quality engine oil fulfil today's requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

TRONICSTAR C2 is especially suitable for use in automobile petrol and diesel engines with subsequent exhaust treatment systems, which require engine oils with a low viscosity (ACEA C2), according to the manufacturer's instructions .

The "low Ash" (Mid SAPS formula low ash content) protects the engine as well as the catalytic converter system.

Properties

- Extreme wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimum loss through friction, more power for the engine
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability
- Maximum shear stability

Effects

- Reduces fuel consumption and exhaust emission
- Formulation for less fuel consumption and Low Ash
- Excellent cold start behaviour - fast supply of all lubrication points, especially of the hydraulic valve tappet
- Stable oil pressure
- Perfect and long lasting engine cleanliness
- Prevents motor from incrustation
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

Suitable for/ we recommend this product for

SAE	5W-30
API	SN/CF/EC
ACEA	C2, A5/B5
ILSAC	GF-5
We recommend this product for:	
FIAT	9.55535-S1
HONDA	
HYUNDAI	
KIA	
MAZDA	
MITSUBISHI	
PSA	B71 2290
RENAULT	RN0700
SUBARU	
TOYOTA	

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with Valvetronic
- with catalyst technology
- Passenger car diesel engines
- with multivalve-technology
- with turbo charging
- with CDi-technology
- with diesel particle systems(DPF)
- with catalyst technology

Disposal:

- **TRONICSTAR C2** is assigned to category 1 of used oils and thus is free for disposal.

Miscibility:

- **TRONICSTAR C2** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **TRONICSTAR C2** it is recommendable to use only **TRONICSTAR C2** when refilling.

TRONICSTAR C2

Article No.	Packaging unit	
309162	Can	1 L
309164	Can	5 L
309165	Can	20 L
309166	Drum	60 L
309168	Drum	200 L
349169	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	851
Dynamic viscosity at -30°C	mPa.s	5390
Viscosity at 40°C	mm ² /s	64,1
Viscosity at 100°C	mm ² /s	11,0
Viscosity index		165
Flash point COC	°C	236
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	8,5

