



# TRONICSTAR C2

Fuel-Economy Mid SAPS-HC-Synthetic-Motor Oil 5W30

## Description:

**TRONICSTAR C2** is a further developed Fuel Economy (FE) HC- synthetic fuel-efficient engine oil with the viscosity SAE 5W-30. The exceptional qualities of this high quality engine oil fulfil today's requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

**TRONICSTAR C2** is especially suitable for use in automobile petrol and diesel engines with subsequent exhaust treatment systems, which require engine oils with a low viscosity (ACEA C2), according to the manufacturer's instructions .

The "low Ash" (Mid SAPS formula low ash content) protects the engine as well as the catalytic converter system.

## Properties

- Extreme wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimum loss through friction, more power for the engine
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability
- Maximum shear stability

## Effects

- Reduces fuel consumption and exhaust emission
- Formulation for less fuel consumption and Low Ash
- Excellent cold start behaviour - fast supply of all lubrication points, especially of the hydraulic valve tappet
- Stable oil pressure
- Perfect and long lasting engine cleanliness
- Prevents motor from incrustation
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

## Suitable for/ we recommend this product for

SAE	5W-30
API	SN/CF/EC
ACEA	C2, A5/B5
ILSAC	GF-5
We recommend this product for:	
FIAT	9.55535-S1
HONDA	
HYUNDAI	
KIA	
MAZDA	
MITSUBISHI	
PSA	B71 2290
RENAULT	RN0700
SUBARU	
TOYOTA	

## Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with Valvetronic
- with catalyst technology
  
- Passenger car diesel engines
- with multivalve-technology
- with turbo charging
- with CDi-technology
- with diesel particle systems(DPF)
- with catalyst technology

## Disposal:

- **TRONICSTAR C2** is assigned to category 1 of used oils and thus is free for disposal.

## Miscibility:

- **TRONICSTAR C2** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **TRONICSTAR C2** it is recommendable to use only **TRONICSTAR C2** when refilling.

**TRONICSTAR C2**

<b>Article No.</b>	<b>Packaging unit</b>	
309162	Can	1 L
309164	Can	5 L
309165	Can	20 L
309166	Drum	60 L
309168	Drum	200 L
349169	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	851
Dynamic viscosity at -30°C	mPa.s	5390
Viscosity at 40°C	mm <sup>2</sup> /s	64,1
Viscosity at 100°C	mm <sup>2</sup> /s	11,0
Viscosity index		165
Flash point COC	°C	236
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	8,5

