



MPG TRIGARD

Long-term radiator coolant concentrate Colour: red

Description:

MPG TRIGARD is made on the basis of eco-friendly propylene glycol concentrate full engine coolant for use in cooling systems of internal combustion engines for the summer and winter, with frost and rust protection (year-round use).

MPG TRIGARD contains high quality corrosion additives and is characterized by optimum corrosion protection for all cooling system used in the metals and metal alloys including aluminum.

MPG TRIGARD is free of nitrite, amine, phosphate and silicate, as well as of organic acids.

MPG TRIGARD provides long term protection against all types of corrosion due to optimized and patented organic corrosion inhibitors. Especially on aluminum surfaces in modern engines a lasting protective effect is guaranteed. The applied inhibitor package provides excellent protection against cavitation.

The previous common "supplemental coolant additives (SCA)" on the basis of nitrite are now no longer required in trucks and buses.

Properties:

- Longer and outstanding protection against corrosion for all metals used in the cooling system and metal alloys including aluminum
- Prevents layer formation and deposits in the cooling system
- Outstanding heat transfer and heat transport
- Compatibility with varnishes
- Compatibility with hose and sealing materials
- Avoidance of foaming
- Environmentally-friendly, biologically degradable
- Suitable for mixed fleets, one product for cars, trucks and construction machinery

Application:

MPG TRIGARD can be used in the cooling system of all-aluminium engines (follow manufacturer's instructions).

The patented silicate-free carboxylate technology provides long-term protection for all materials used in motor, especially for aluminum and iron alloys.

Recommended concentration 50% **MPG TRIGARD** and 50% water, in which protection against freezing up to -37°C is achieved.

MPG TRIGARD is a long-life coolant and can be used in vehicles for a lifetime filling.

Duration of use:

Commercial Vehicles up to 650,000 km (about 8,000 hours)

Cars up to 250,000 km (about 2,000 hours)

Stationary engines up to 32,000 hours (or 6 years)

It is recommended to change the coolant earliest every 5 years or, if the achievement of the above mentioned periods.

Reliable in practice and tested for many years.

Suitable for/ we recommend this product for:

We recommend this product for:	
ASTM	D 3306
ASTM	D 4985
BS	6580

Miscibility:

- **MPG TRIGARD** can be mixed with the most of the coolants based on ethylene glycol. To achieve an optimal corrosion protection and to avoid sludge formation it is recommended to use pure **MPG TRIGARD**. For the preparation of mixtures softened water should be preferred.

Data are subject to change.

Attention: Service instructions should be observed!

KC/WI/"/"
09/2016

MPG TRIGARD

Article No.	Packaging unit	
510155	Can	20 L
510156	Drum	60 L
510158	Drum	200 L
510159	PE-Container	1000 L

Typical characteristics:

Specific weight at 20°C	kg/m ³	1.00 - 1.042
Flash point COC	°C	>100
Boiling point	°C	>165
ph-value	50 Vol.%	8,8
Water Content	%	4 max.
Pour point antifreeze/water = 1:1		>-33°C
Other glycols	%	0,5 max.
Propylene glycol	%	93,0
Content of inhibitors	%	5
Ash content	%	1,4
Reserve alkalinity	(pH 5,5)	6,3
Colour		Red

