

CORONA XH4

Hightec-HC-Synthetic-Motor Oil 5W40

Description:

CORONA XH4 is a high-tech, HC synthetic engine oil which has been developed for petrol and diesel car engines, and is ideal for modern updated fuel injection and turbo engines.

CORONA XH4 meets the high quality requirements of the car manufacturers. It is excellently applicable for long oil change intervals.

Ideal for hard use at motorways and over short distances.

Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxydation- and thermo stability

Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Lowest oil consumption
- High margin of performance and high product stability
- Extended oil change intervals
- Prevents black sludge formation
- All-year operation

Suitable for/ we recommend this product for

| | |
|--------------------------------|--------------------|
| SAE | 5W-40 |
| API | SN/CF/EC |
| ACEA | A3/B4 |
| We recommend this product for: | |
| BMW | Longlife-01 |
| FIAT | 9.55535-M2, H2, N2 |
| MB | 229.3 |
| OPEL | GM-LL-B-025 |
| PORSCHE | A40 |
| PSA | B71 2296 |
| RENAULT | RN0700/0710 |
| VW | 502.00, 505.00 |

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal:

- **CORONA XH4** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **CORONA XH4** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **CORONA XH4** it is recommendable to use only **CORONA XH4** when refilling.

CORONA XH4

| Article No. | Packaging unit | |
|-------------|----------------|--------|
| 1200 622 | Can | 1 L |
| 1200 623 | Can | 4 L |
| 1200 624 | Can | 5 L |
| 1200 625 | Can | 20 L |
| 1200 626 | Drum | 60 L |
| 1200 628 | Drum | 200 L |
| 1240 629 | PE-Container | 1000 L |

Typical characteristics:

| | | |
|----------------------------|--------------------|------|
| Specific weight at 15°C | kg/m ³ | 854 |
| Dynamic viscosity at -30°C | mPa.s | 6060 |
| Viscosity at 40°C | mm ² /s | - |
| Viscosity at 100°C | mm ² /s | 14,7 |
| Viscosity index | | 173 |
| Flash point COC | °C | 226 |
| Pourpoint | °C | -42 |
| Sulphate ashes | % | - |
| TBN | mgKOH/g | 10,5 |

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-
08/2021