

# **OREGON BX**

S.T.O.U. Special Tractor-Oil 10W30

#### **Description:**

**OREGON BX** is a special oil which meets the recommendations of all well known tractor manufacturers. It can be used equally for engines, gears and hydraulic systems of modern tractors. High-quality basic oils and selected additives provide a disturbance-free operation of all units at all seasons. Thus also best suitable for wet brakes and clutches (power shaft clutches).

## **Properties**

- · Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

# Suitable for/ we recommend this product for

SAE (engine)	10W-30		
SAE (Gear box)	80W		
ACEA	E3		
API	CF/CG-4/SF		
API	GL-4		
DIN 51524/3	HVLP-D 68		
We recommend this product for:			
ALLISON	C-4		
CASE NH	MAT 3525/3526		
CATERPILLAR	TO-2		
FORD	M2C159-B/C		
JOHN DEERE	JDM 27		
MASSEY FERGUSON	M 1139, 1144, 1145		
MB	227.1		
MB	228.1		
ZF	TE-ML 06A/B/C,07B		

## **Effects**

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- All-year operation
- Excellent cold starting behaviour

#### Utilization

All kinds of agricultural machines

## Disposal:

• OREGON BX is assigned to category 2 of used oils and thus is free for disposal.

#### Miscibility:

 OREGON BX is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only OREGON BX when refilling.

ackaging unit
0 0
n 20 L
rum 60 L
rum 200 L
E-Container 1000 L

Typical characteristics:		
Specific weight at 15°C	kg/m³	864
Dynamic viscosity at -25°C	mPa.s	5820
Viscosity at 40°C	mm²/s	71,0
Viscosity at 100°C	mm²/s	10,8
Viscosity index		140
Flash point COC	°C	224
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	10,7

Data are subject to change. Attention: Service instructions should be observed!