

# OREGON CX

**S.T.O.U. Lightrun-Special Tractor-Oil 10W40**

## Description:

**OREGON CX** is a universal high-performance STOU oil which meets the recommendations of all well known tractor producers. By its viscosity adjustment SAE 10W/40 a quick lubrication of all aggregates is guaranteed. The stable lubricating film protects against wear also at high temperatures.

**OREGON CX** can be used for motors, gears and hydraulic systems of modern tractors and is also best suitable for wet brakes and clutches (journal clutches).

## Properties

- Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

## Effects

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- Excellent cold starting properties - rapid supply of all points of lubrication
- Suitable for extended oil change intervals
- All-year operation

## Suitable for/ we recommend this product for

SAE	10W-40
SAE	90
ACEA	E3
API	CF/CG-4/SF
API	GL-4
DIN 51524/3	HVLP-D 68
We recommend this product for:	
ALLISON	C-4
CASE NH	MAT 3525/3526, 410B
CATERPILLAR	TO-2
FENDT	KDM 41.2011
FORD	M2C159-B/C, M2C134-B/C/D
JOHN DEERE	JDM 27, J20C/D
MAN	271
MASSEY FERGUSON	CMS, M 1139/1144/1145
MB	227.1
MB	228.1
NEW HOLLAND	NH 410B
ZF	TE-ML 06A/B/C/D/F, 07B

## Utilization

- All kinds of agricultural machines

## Disposal:

- **OREGON CX** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **OREGON CX** is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only **OREGON CX** when refilling.

## OREGON CX

Article No.	Packaging unit	
1201 735	Can	20 L
1201 736	Drum	60 L
1201 738	Drum	200 L
1241 739	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	865
Dynamic viscosity at -25°C	mPa.s	6270
Viscosity at 40°C	mm <sup>2</sup> /s	96,9
Viscosity at 100°C	mm <sup>2</sup> /s	14,5
Viscosity index		148
Flash point COC	°C	226
Pourpoint	°C	-39
TBN	mgKOH/g	10,8

