



# GALAXIS EXTRA 3

Hightec-HC-Synthetic-Motor Oil 10W40

# **Description:**

**GALAXIS EXTRA 3** is a complex, high-performance, low-friction passenger car petrol and diesel engine oil of the latest generation. The use of high-quality HC-Synthetic components and high-quality mineral base oils, combined with the latest technology additives, **GALAXIS EXTRA 3** engine oil is excellently suited for use in modern car engines with and without turbochargers and for light commercial vehicles, even under harsh operating conditions.

GALAXIS EXTRA 3 ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

# **Properties**

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- · Very high cleaning capability
- Low volatilization loss

### \_\_\_

- Very good operating reliability
- Excellent cold starting properties rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Reduced oil consumption
- All-year operation

# Suitable for/ we recommend this product for

SAE	10W-40			
API	SN/CF/EC			
ACEA	A3/B4			
We recommend this product for:				
MB	229.3			
MB	229.1			
PSA	B71 2296			
RENAULT	RN0700	·		
VW	502.00, 505.00	•		

# Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- · with turbo charging
- with catalyst technology
- Passenger car- and light commercial vehicle diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- · with CDi-technology
- Direct-injection
- with catalyst technology

# Disposal:

• GALAXIS EXTRA 3 is assigned to category 2 of used oils and thus is free for disposal.

# Miscibility:

• GALAXIS EXTRA 3 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take GALAXIS EXTRA 3 when refilling.

GALAXIS EXTR	A 3	
Article No.	Packaging unit	
<mark>3</mark> 00 942	Can	1 L
<mark>30</mark> 0 943	Can	4 L
300 944	Can	5 L
300 945	Can	20 L
300 946	Drum	60 L
300 948	Drum	200 L
340 949	PE-Container	1000 L

Typical characteristics:		
Specific weight at 15°C	kg/m³	860
Dynamic viscosity at -25°C	mPa.s	<mark>53</mark> 70
Viscosity at 40°C	mm²/s	93,3
Viscosity at 100°C	mm²/s	14,6
Viscosity index		163
Flash point COC	°C	232
Pourpoint	°C	-42
TBN	mgKOH/g	10,6

Data are subject to change.

KL/MO/PKW/Attention: Service instructions should be observed!

KL/MO/PKW/07/2021