

PHOENIX 1000

Fully Synthetic-Motor Oil 10W60

Description:

PHOENIX 1000 is a fully synthetic engine oil for highly loaded petrol and diesel car engines, particularly for uprated fuel injection and turbo engines.

PHOENIX 1000 is ideal for engines which are submitted to hardest conditions in motor sports.

With its broad viscosity SAE 10W-60 extremely high temperature stability can be assured.

PHOENIX 1000 is particularly suitable for use in motorcycles with 4-stroke engines to recommend both on-road and off-road.

Properties

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- High cleaning capability
- High oxidation and temperature stability
- Prevents black sludge formation

Effects

- Excellent cold starting behaviour
- Very good operating reliability
- Optimises motor performance
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability
- All-year operation

Suitable for/ we recommend this product for

| | |
|--------------------------------|----------------|
| SAE | 10W-60 |
| API | SN/CF |
| ACEA | A3/B4 |
| We recommend this product for: | |
| BMW | M Series |
| FIAT | 9.55535-H3 |
| MB | 229.1 |
| VW | 501.00, 505.00 |

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- and TDI motors
- Direct-injection
- with catalyst technology
- Motorcycles with 4-stroke engines

Disposal:

- **PHOENIX 1000** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **PHOENIX 1000** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **PHOENIX 1000** it is recommendable to use only **PHOENIX 1000** when refilling.

PHOENIX 1000

| Article No. | Packaging unit | |
|-------------|----------------|-------|
| 1200 982 | Can | 1 L |
| 1200 984 | Can | 5 L |
| 1200 985 | Can | 20 L |
| 1200 986 | Drum | 60 L |
| 1200 988 | Drum | 200 L |

Typical characteristics:

| | | |
|----------------------------|--------------------|------|
| Specific weight at 15°C | kg/m ³ | 859 |
| Dynamic viscosity at -25°C | mPa.s | 5410 |
| Viscosity at 40°C | mm ² /s | 180 |
| Viscosity at 100°C | mm ² /s | 25,8 |
| Viscosity index | | 180 |
| Flash point COC | °C | 226 |
| Pourpoint | °C | -42 |
| TBN | mgKOH/g | 13,6 |