

ONTARIO FD

Fuel-Economy-Mid SAPS-HC-Synthetic-High-Performance-Motorenoil 0W-30

Description:

ONTARIO FD is a further developed fuel economy Mid Saps HC- synthetic high performance engine oil. Because of the low SAPS content this engine oil is perfectly suitable for vehicles with modern three- way catalysts and diesel particle filters.

ONTARIO FD is recommended for use in Ford engines when the Ford specification WSS-M2C950-A with the viscosity SAE 0W30 is instructed.

Properties

- Extrem wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion
- Improved carbon absorption
- Good resistance to bio diesel-shares in the fuel

Effects

- Reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission
- Excellent cold starting behaviour
- Very good operating reliability
- Optimal engine cleanliness
- Very low oil consumption
- High margin of performance and high product stability, also at extended oil change intervals
- All-year operation

Suitable for/ we recommend this product for

SAE	0W-30
ACEA	C2
We recommend this product for:	
FIAT	9.55535-GS1/DS1
FORD	WSS-M2C950-A
JAGUAR/LAND ROVER	STJLR.03.5007

Utilization

- High-performance and normal four-stroke petrol engines
 - with multivalve technology
 - with turbo charging
 - with catalyst technology
- Passenger car-high-performance- and normal four-stroke diesel-engine
 - with multivalve-technology
 - with turbo charging
 - with CDi-technology
 - with diesel particle systems(DPF)
 - with catalyst technology

Disposal:

- **ONTARIO FD** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **ONTARIO FD** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **ONTARIO FD** it is recommendable to use only **ONTARIO FD** when refilling.

ONTARIO FD

Article No.	Packaging unit	
1209 392	Can	1 L
1209 393	Can	4 L
1209 394	Can	5 L
1209 395	Can	20 L
1209 396	Drum	60 L
1209 398	Drum	200 L
1249 399	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	844
Dynamic viscosity at -35°C	mPa.s	5620
Viscosity at 40°C	mm ² /s	53,9
Viscosity at 100°C	mm ² /s	10,4
Viscosity index		185
Flash point COC	°C	230
Pourpoint	°C	-45
Sulphate ashes	%	-
TBN	mgKOH/g	-

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-
04/2020