



GALAXIS EXTRA 2

Semi-Synthetic-Motor Oil 10W40

Description:

GALAXIS EXTRA 2 is an highly alloyed semi synthetic lightrun petrol and diesel engine oil enabling by its additives, selection of base oils and its viscosity application an energy-saving operation of car diesel engines. To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss **GALAXIS EXTRA 2** lightrun engine contains synthetic components meeting the demands of high tech.

Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption
- All-year operation

Suitable for/ we recommend this product for

SAE	10W-40
API	SL/CF/EC
ACEA	A3/B4
We recommend this product for:	
MB	229.1
PSA	B71 2296
RENAULT	RN0700
VW	505.00

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Suction diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal:

- **GALAXIS EXTRA 2** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **GALAXIS EXTRA 2** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **GALAXIS EXTRA 2** when refilling.

GALAXIS EXTRA 2

Article No.	Packaging unit	
300902	Can	1 L
300903	Can	4 L
300904	Can	5 L
300905	Can	20 L
300906	Drum	60 L
300908	Drum	200 L
340909	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m³	856
Dynamic viscosity at -25°C	mPa.s	4240
Viscosity at 40°C	mm²/s	95,4
Viscosity at 100°C	mm²/s	15,0
Viscosity index		166
Flash point COC	°C	232
Pourpoint	°C	-39
Sulphate ashes	%	-
TBN	mgKOH/g	10,3

Data are subject to change.

Attention: Service instructions should be observed!

KL/MO/PKW/-/-
07/2021