



# BAROS (HLP 46)

HLP-Hydraulic Oil according DIN 51524, Part 2

## Description:

**BAROS (HLP 46)** is optimum alloyed and is having a high performance level as well as a broad field of application within the whole industry. It especially distinguish with good viscosity-temperature behaviour, high ageing stability and reliable corrosion protection. Effective additives provides an excellent wear protection under extreme loads. too (FZG-Test A/8,3/90 12 th damage loading step). The behaviour against sealing materials is neutral).

## Properties

- High pressure susceptibility
- Excellent wear protection
- High air and water separating property
- Very good viscosity temperature behaviour
- High ageing stability
- Reliable protection against corrosion
- Neutral towards sealing materials

## Effects

- High operation safety of hydraulic equipment
- Favourable operating properties
- High performance level

## Suitable for/ we recommend this product for

DIN 51524/2	ISO VG 46 / HLP 46
ISO 11158	HM
AFNOR	NF E 48-603 (HM)
MIL	H 24 459
ASTM	D6158
SAE	MS 1004
We recommend this product for:	
AIST	127, 136
ASLE	70-1/70-2/70-3
BOSCH	Rexroth
CETOP	RP 91 H (HM)
CINCINNATI MILACRON	P 70
DAVID BROWN	ET 19, ET 33
DENISON	HF-0, HF-2
EATON VICKERS	M 2950-S / I-286-S3
FZG Test	A8, 3/90 12th damage loading step
GM	LS 2
HOESCH	HWN 2333
JCMAS	P041 HK
SAUER DANFOSS	520L0463
SEB	181222 (HLP 46)
SIS	SS 155434
US STEEL	126/127
VDMA	24318

## Utilization

- Hydraulic equipment according DIN 51524
- for example: mobil hydraulics, pressing and forging plants, splash-pour-machines, a.o.

## Disposal:

- **BAROS (HLP 46)** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **BAROS (HLP 46)** of HLP range is well-tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **BAROS (HLP 46)** of HLP range when refilling.

Data are subject to change.

Attention: Service instructions should be observed!

KL/HY/-/-  
02/2023

**BAROS (HLP 46)**

<b>Article No.</b>	<b>Packaging unit</b>	
303002	Can	1 L
303004	Can	5 L
303005	Pail	20 L
303006	Drum	60 L
303008	Drum	200 L
343009	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	864
Viscosity at 40°C	mm <sup>2</sup> /s	45
Viscosity at 100°C	mm <sup>2</sup> /s	7,0
Viscosity index		116
Flash point COC	°C	240
Pourpoint	°C	-30
TAN	mgKOH/g	-

