



MEHRZWECK-FETT

Universal Grease

Description:

MEHRZWECK-FETT is a natural-coloured, lithium saponified lubrication grease of NLGI category 2 with additives for improvement of corrosion protection, ageing stability of lubrication film and the adhesion ability.

MEHRZWECK-FETT is for the lubrication of sliding and rolling bearings as well as for sliding surfaces within a temperature range of -30°C to +130°C, at normal conditions and for all for grease lubrication permitted sliding speeds.

It also serves as grease lubrication for vehicles, construction machinery and agricultural equipment and guarantees a long-term grease lubrication as well as good sealing. It is stable a wet and dusty surroundings.

Properties

- Good adhesion ability
- High pressure susceptibility
- Oxidation stability
- Ageing stability
- Corrosion protecting
- Cold and hot water resistant
- Especially stable to milling

Effects

- Universally usable
- Excellent lubrication properties
- Efficient
- The high temperature range provides reduction of sort variety

Technical data

Typical characteristics:

| | |
|-------------------|------------------|
| Temperature range | -30 up to +120°C |
| Short-termed | up to +130°C |
| Drop point | > 180°C |
| NLGI-category | 2 |
| Term (DIN 51502): | K2K-30 |
| ISO 12924: | L-XC(F)CAA2 |

Examples of use:

Axle bearings, roller bearings at electric motors, machine tools, wheel hubs, long-life lubricated passenger car suspension, conveyor roller bearings etc.

MEHRZWECK-FETT

| Article No. | Packaging unit | |
|-------------|----------------|--------|
| 310021 | Cartridge | 400 g |
| 310002 | Can | 1 kg |
| 310003 | Bucket | 5 kg |
| 310007 | Jokey | 18 kg |
| 310005 | Large tin can | 25 kg |
| 310006 | Drum | 50 kg |
| 310008 | Drum | 180 kg |

Data are subject to change.

Attention: Service instructions should be observed!

KL/FE/-/-
10/2018