



MEGA TRUCK 2

Heavy Duty-Multigrade-Motor Oil 15W40

Description:

MEGA TRUCK 2 is a very high categorized SHPD engine oil that meets the required emissions standards.

MEGA TRUCK 2 is thus recommended for the Euro 2, Euro 3, Euro 4 and Euro 5 motor generation with EGR and/or SCR technology (not for engines with particle filter).

MEGA TRUCK 2 is a universally usable all-year engine oil for all suction and charged diesel engines. Usable for all, also under very extreme operation conditions. Also suitable for use in passenger car engines.

MEGA TRUCK 2 meets the requirements of extended oil changing intervals (please observe manufacturers' instructions).

Properties

- Exceptional high detergent effect which almost prevents residues in the combustion section
- Formation of cold sludge and residues in the engine and the oil pan are nearly prevented
- Optimal protection against corrosion, oxidation, wear and foaming
- Extremely high pressure susceptibility
- Very well cleaning capability
- Excellent ageing stability
- Excellent viscosity-temperature behaviour

Effects

- High operating reliability
- Very well suitable for difficult operating conditions
- Suitable for longest oil changing intervals
- Prevents black sludge formation
- Protection against reflector surface formation
- Improved economy viability by extended inspections-intervals
- Minimum wear at highly strained engines
- High stable viscosity index
- All-year operation
- Reduction of kinds

Suitable for/ we recommend this product for

SAE	15W-40
API	CI-4/SL + SHPD
ACEA	E7
We recommend this product for:	
CATERPILLAR	ECF-1, ECF-2
CUMMINS	CES 20077/78
DETROIT DIESEL	93K215
DEUTZ	DQC III-10
GLOBAL	DHD-1
JASO	DH1
MACK	EO-M Plus, EO-N
MAN	M 3275
MB-Approval	228.3
MTU	Type 2
RENAULT	RLD-1, RLD-2
VOLVO	VDS-3

Utilization

- Commercial vehicle diesel engines
 - with turbo charging
 - with catalyst technology
 - with EGR technology
 - with SCR technology
- Passenger car diesel engines
 - with turbo charging
 - with catalyst technology
- Four-stroke petrol engines
 - with turbo charging
 - with catalyst technology
- Work and agricultural machinery diesel engines

Disposal:

- **MEGA TRUCK 2** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **MEGA TRUCK 2** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **MEGA TRUCK 2** only.

MEGA TRUCK 2

Article No.	Packaging unit	
300424	Can	5 L
300425	Can	20 L
300426	Drum	60 L
300428	Drum	200 L
340429	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	862
Dynamic viscosity at -20°C	mPa.s	3720
Viscosity at 40°C	mm ² /s	94,9
Viscosity at 100°C	mm ² /s	14,5
Viscosity index		158
Flash point COC	°C	232
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	11,3

