



# S-TRONIC PLUS

**Hightec-HC-Synthetic-Motor Oil 5W30**

## Description:

**S-TRONIC PLUS** is a hightec synthetic lightrun motor oil especially developed for heavily stressed petrol and diesel car motors.

**S-TRONIC PLUS** meets the manufacturers`high quality demands for cars. It is excellently applicable for long oil changing intervals and for motors with direct injection.

Ideal for hard use at motorways and over short distances.

## Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

## Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Lowst oil consumption
- High margin of performance and high product stability
- Extended oil change intervals
- Prevents black sludge formation
- All-year operation

## Suitable for/ we recommend this product for

SAE	5W-30
API	SN/CF/EC
ACEA	A3/B4
We recommend this product for:	
BMW	Longlife-98
GM	LL-B-025
MB	229.3
PORSCHE	approved
VW	502.00, 505.00

## Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Direct-injection
- with CDi-technology
- with catalyst technology

## Disposal:

- **S-TRONIC PLUS** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **S-TRONIC PLUS** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **S-TRONIC PLUS** it is recommendable to use only **S-TRONIC PLUS** when refilling.

S-TRONIC PLUS		
Article No.	Packaging unit	
300362	Can	1 L
300363	Can	4 L
300364	Can	5 L
300365	Can	20 L
300366	Drum	60 L
300368	Drum	200 L
340369	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	850
Dynamic viscosity at -30°C	mPa.s	4420
Viscosity at 40°C	mm <sup>2</sup> /s	63,8
Viscosity at 100°C	mm <sup>2</sup> /s	10,9
Viscosity index		171
Flash point COC	°C	230
Pourpoint	°C	-42
TBN	mgKOH/g	10,5