



TRAKTOR EXO 3

S.T.O.U. Special Tractor-Oil 10W30

Description:

TRAKTOR EXO 3 is a special oil which meets the recommendations of all well known tractor manufacturers. It can be used equally for engines, gears and hydraulic systems of modern tractors. High-quality basic oils and selected additives provide a disturbance-free operation of all units at all seasons. Thus also best suitable for wet brakes and clutches (power shaft clutches).

Properties

- Reduces formation of ageing products at high temperatures
- Neutralizes acids emerging from fuel combustion
- First-rate anti-volatilization behaviour
- High ageing stability
- Excellent viscosity-temperature behaviour

Suitable for/ we recommend this product for

SAE (engine)	10W-30		
SAE (gear box)	80W		
ACEA	E3		
API	CF/CG-4/SF		
API	GL-4		
DIN 51524/3	HVLP-D 68		
We recommend this product for:			
ALLISON	C-4		
CASE NH	MAT 3525/3526		
CATERPILLAR	TO-2		
FORD	M2C159-B/C		
JOHN DEERE	JDM 27		
MASSEY FERGUSON	M 1139, 1144, 1145		
MB	227.1		
MB	228.1		
ZF	TE-ML 06A/B/C,07B		

Effects

- Optimal operating properties
- Provides disturbancefree operation of all engines, gears, hydraulic and brake units
- Good balanced friction behaviour at wet brakes and gears
- All-year operation
- Excellent cold starting behaviour

Utilization

· All kinds of agricultural machines

Disposal:

• TRAKTOR EXO 3 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• TRAKTOR EXO 3 is only miscible with comparable lubrications and well tolerated. However, it is recommended to take only TRAKTOR EXO 3 when refilling.

TRAKTOR EXO	3	
Article No.	Packaging unit	
<mark>3</mark> 01715	Can	20 L
<mark>30</mark> 1716	Drum	60 L
3 <mark>01</mark> 718	Drum	200 L
341719	PE-Container	1000 L

Typical characteristics:		
Specific weight at 15°C	kg/m³	864
Dynamic viscosity at -25°C	mPa.s	5820
Viscosity at 40°C	mm²/s	71,0
Viscosity at 100°C	mm²/s	10,8
Viscosity index		140
Flash point COC	°C	224
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	10,7

Data are subject to change.

KL/MO/TR/-/Attention: Service instructions should be observed!

KL/MO/TR/-/07/2021