



# G-TEC 1000

**Fully Synthetic-Motor Oil 10W60**

## Description:

**G-TEC 1000** is a fully synthetic engine oil for highly loaded petrol and diesel car engines, particularly for uprated fuel injection and turbo engines.

**G-TEC 1000** is ideal for engines which are submitted to hardest conditions in motor sports.

With its broad viscosity SAE 10W-60 extremely high temperature stability can be assured.

**G-TEC 1000** is particularly suitable for use in motorcycles with 4-stroke engines to recommend both on-road and off-road.

## Properties

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- High cleaning capability
- High oxidation and temperature stability
- Prevents black sludge formation

## Effects

- Excellent cold starting behaviour
- Very good operating reliability
- Optimises motor performance
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability
- All-year operation

## Suitable for/ we recommend this product for

SAE	10W-60
API	SN/CF
ACEA	A3/B4
We recommend this product for:	
BMW	M Series
FIAT	9.55535-H3
MB	229.1
VW	501.00, 505.00

## Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- and TDI motors
- Direct-injection
- with catalyst technology
- Motorcycles with 4-stroke engines

## Disposal:

- **G-TEC 1000** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **G-TEC 1000** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **G-TEC 1000** it is recommendable to use only **G-TEC 1000** when refilling.

## G-TEC 1000

Article No.	Packaging unit	
300982	Can	1 L
300984	Can	5 L
300985	Can	20 L
300986	Drum	60 L
300988	Drum	200 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	859
Dynamic viscosity at -25°C	mPa.s	5410
Viscosity at 40°C	mm <sup>2</sup> /s	180
Viscosity at 100°C	mm <sup>2</sup> /s	25,8
Viscosity index		180
Flash point COC	°C	226
Pourpoint	°C	-42
TBN	mgKOH/g	13,6

Data are subject to change.

Attention: Service instructions should be observed!

KL/MO/PKW/-/-  
04/2020