



AIRMEXX PAO 68

Synthetic ammonia air conditioning liquid

Description:

AIRMEXX PAO 68 is a synthetic air conditioning liquid on the basis of PAO.

AIRMEXX PAO 68 is ideal for the lubrication of compressors in ammonia cooling systems.

Properties

- Fully compatible with ammonia
- Contains a minimum of additives
- Prevents sedimentation in low temperature systems
- Reduces sedimentations in the exhaust valve
- Excellent lubricity
- No wax content
- Low vaporization
- Very low steam pressure either steam tension
- Non-hygroscopic

Effects

- Increases the efficiency of air conditionings
- Highest operating reliability

Suitable for/ we recommend this product for

ISO-GRADE 68 AA1

Utilization

- Reciprocating compressors and screw compressors that are used in ammonia systems
- Gas compressors and vacuum-pump-systems, where ammonia fumes develop
- Geeignet für den Einsatz mit folgenden Gasen: R717, R290, R22, R134a, R1234yf

Miscibility:

- AIRMEXX PAO 68 is fully mixable with customary mineral oils. However, it is recommendable to use AIRMEXX PAO 68 only.

AIRMEXX PAO 68

Article No.	Packaging unit	
320141	Can	500 ml
320142	Can	1 L

Typical characteristics:

Specific weight at 20°C	kg/m ³	833
Viscosity at 40°C	cSt	63,9
Viscosity at 100°C	cSt	-
Viscosity index		139
Flash point COC	°C	-
Pourpoint	°C	<-45
ISO-grade		68