

COSTA 1050

Multigrade-Motor Oil 15W40

Description:

COSTA 1050 is a multigrade engine oil for the use in petrol and diesel engines. The favourable SAE category 15W/40 provides an unproblematic operation at all seasons.

COSTA 1050 is usable as all-seasons oil.

Properties

- Multigrade engine oil
- Excellent viscosity-temperature behaviour
- Selected additives guarantee a good engine lubrication
- High safety potential, also at boundary lubrication conditions

Suitable for/ we recommend this product for

| | |
|-----|--------|
| SAE | 15W-40 |
| API | SF/CD |

Effects

- All-year operation
- Good cold starting properties
- High operating reliability
- Prevents black sludge formation

Utilization

- Four-stroke petrol engines
- with turbo charging
- with catalyst technology
- diesel engines
- with turbo charging
- with catalyst technology

Disposal:

- **COSTA 1050** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **COSTA 1050** is fully compatible to comparable lubrications and can be mixed without any doubts.

COSTA 1050

| Article No. | Packaging unit | |
|-------------|----------------|--------|
| 1200 102 | Can | 1 L |
| 1200 104 | Can | 5 L |
| 1200 105 | Can | 20 L |
| 1200 106 | Drum | 60 L |
| 1200 108 | Drum | 200 L |
| 1240 109 | PE-Container | 1000 L |

Typical characteristics:

| | | |
|----------------------------|--------------------|------|
| Specific weight at 15°C | kg/m ³ | 857 |
| Dynamic viscosity at -20°C | mPa.s | 2460 |
| Viscosity at 40°C | mm ² /s | 90,8 |
| Viscosity at 100°C | mm ² /s | 14,4 |
| Viscosity index | | 165 |
| Flash point COC | °C | 226 |
| Pourpoint | °C | -45 |
| Sulphate ashes | % | - |
| TBN | mgKOH/g | 6,5 |