

TACOMA SPECIAL

Chain Saw Adhesive Lubrication Oil Mineral Oil based

Description:

TACOMA SPECIAL Chain Saw adhesive lubrication oil is a product for power saw chain proved in practice. Because of well chosen additive combinations an excellent adhesition with very good temperature behaviour and good lubrication properties is provided.

TACOMA SPECIAL Chain Saw adhesive lubrication oil thus is best suitable for summer and winter operation. The very good cooling effect ensures low wear at optimum cutting speed. It is neutral against sealing materials, plastic and paintwork and at the same time this product protects agianst corrosion.

Effects

Highest operational height

Best suitable for summer and winter operation

Properties

- · Excellent temperature behaviour
- High adhesive behaviour
- Good lubrication properties
- · High wear protection
- Neutral towards coating of power saws
- Reliable corrosion protection
- Very good cooling effect
- Colour dark

Utilization:

- All brands of power chain saws
- Saw frame
- Transport bearings
- Withdrawing device
- Rope guide
- Rack
- JointsSliding
- shaing • etc.

Disposal:

TACOMA SPECIAL is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

TACOMA SPECIAL is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **TACOMA SPECIAL** only.

TACOMA SPECI	AL	
Article No.	Packaging unit	
1206 202	Can	1 L
1206 204	Can	5 L
1206 205	Can	20 L
1 <mark>206 206</mark>	Drum	60 L
12 <mark>06 208</mark>	Drum	200 L
1246 209	PE-Container	1000 L

Typical characteristics:			
Specific weight at 15°C	kg/m³	870	
Viscosity at 40°C	mm²/s	103	
Flash point COC	°C	205	
Pourpoint	°C	<-30	

Data are subject to change. Attention: Service instructions should be observed! DV/SO/-05/2018

Kuttenkeuler GmbH • D-50996 Köln • Fon +49 (0) 2236 96203-0 • Fax +49 (0) 2236 96203-27 vertrieb.schmierstoffe@kuttenkeuler.com • www.kuttenkeuler.com