

# FONTANA D2

## Universal Grease

### Description:

**FONTANA D2** is a natural-coloured, lithium saponified lubrication grease of NLGI category 2 with additives for improvement of corrosion protection, ageing stability of lubrication film and the adhesion ability.

**FONTANA D2** is for the lubrication of sliding and rolling bearings as well as for sliding surfaces within a temperature range of -30°C to +130°C, at normal conditions and for all for grease lubrication permitted sliding speeds.

It also serves as grease lubrication for vehicles, construction machinery and agricultural equipment and guarantees a long-term grease lubrication as well as good sealing. It is stable a wet and dusty surroundings.

### Properties

- Good adhesion ability
- High pressure susceptibility
- Oxidation stability
- Ageing stability
- Corrosion protecting
- Cold and hot water resistant
- Especially stable to milling

### Effects

- Universally usable
- Excellent lubrication properties
- Efficient
- The high temperature range provides reduction of sort variety

### Technical data

Typical characteristics:

Temperature range	-30 up to +120°C
Short-termed	up to +130°C
Drop point	> 180°C
NLGI-category	2
Term (DIN 51502):	K2K-30
ISO 12924:	L-XC(F)CAA2

### Examples of use:

Axle bearings, roller bearings at electric motors, machine tools, wheel hubs, long-life lubricated passenger car suspension, conveyor roller bearings etc.

### FONTANA D2

Article No.	Packaging unit	
1210 021 (310 021)	Cartridge	400 g
1210 002	Can	1 kg
1210 003	Bucket	5 kg
1210 007	Jokey	18 kg
1210 005	Large tin can	25 kg
1210 006	Drum	50 kg
1210 008	Drum	180 kg

Data are subject to change.

Attention: Service instructions should be observed!

DV/FE/-  
10/2018