

# FONTANA D2CLX

Special wheelbearing-grease (Colour: blue)

## Description:

**FONTANA D2CLX** is a blue-coloured, high-quality lithium complex grease.

Outstanding mechanical and EP qualities are achieved through the balanced coordination of the complex-soap of the base oil and the additive.

**FONTANA D2CLX** has excellent qualities in regard to bearing capacity, and corrosion and wear protection.

The lithium complex soap enables use within a very wide temperature range, in particular if increased temperatures are created.

**FONTANA D2CLX** has all-around qualities. Therefore this product is the first choice in different operating conditions for ball bearings, heavy loads, and the highest temperature demands, up to 220°C. This grease sets new standards in use a universal-grease in industrial and automotive applications.

## Technical data

Typical characteristics:

Compaction repellent		Lithium complex
Roll penetration 0,1 mm		
NLGI classification	DIN ISO 2137	2
after 60 strokes	DIN ISO 2137	265-295
after 100.000 strokes	DIN ISO 2137	+30
SKM Emscor WWO Dest. water	DIN ISO 11007	0-1
SKF Emscor		
SKF Emscor WWO saltwater	DIN ISO 11007	2-3
Copper corrosion 24h/100°C	ASTM D-4048	1a
Water resistant	DIN 51807/1	1-90
Water washout 1h/80°C	DIN ISO 11009	4 %
SKF R2F Test A	SKF	passed
SKF R2F Test B (140°C)	SKF	passed
Recommended operating temperature		-30°C to +140°C
Recommended operating temperature		Max. +220°C
Name (DIN 51502):		KP2N-30

## FONTANA D2CLX

Article No.	Packaging unit	
1210 741 (310 741)	Cartridge	400 g
1210 732	Can	1 kg
1210 733	Bucket	5 kg
1210 737	Jokey	18 kg
1210 735	Large tin can	25 kg

Data are subject to change.

Attention: Service instructions should be observed!

DV/FE/-  
10/2018