

AIROI PAO (PAO 68)

Synthetic ammonia air conditioning liquid

Description:

AIROI PAO (PAO 68) is a synthetic air conditioning liquid on the basis of PAO.

AIROI PAO (PAO 68) is ideal for the lubrication of compressors in ammonia cooling systems.

Properties

- Fully compatible with ammonia
- Contains a minimum of additives
- Prevents sedimentation in low temperature systems
- Reduces sedimentations in the exhaust valve
- Excellent lubricity
- No wax content
- Low vaporization
- Very low steam pressure either steam tension
- Non-hygroscopic

Effects

- Increases the efficiency of air conditionings
- Highest operating reliability

Suitable for/ we recommend this product for

ISO-GRADE 68 AA1

Utilization

- Reciprocating compressors and screw compressors that are used in ammonia systems
- Gas compressors and vacuum pump-systems, where ammonia fumes develop
- Geeignet für den Einsatz mit folgenden Gasen: R717, R290, R22, R134a, R1234yf

Miscibility:

- AIROI PAO (PAO 68) is fully mixable with customary mineral oils. However, it is recommendable to use AIROI PAO (PAO 68) only.

AIROI PAO (PAO 68)

Article No.	Packaging unit	
1220 141	Can	500 ml
1220 142	Can	1 L

Typical characteristics:

Specific weight at 20°C	kg/m ³	833
Viscosity at 40°C	cSt	63,9
Viscosity at 100°C	cSt	-
Viscosity index		139
Flash point COC	°C	-
Pourpoint	°C	<-45
ISO-grade		68