

CARY CHS 22

Multi-function mineral special hydraulic fluid colour: green

Description:

CARY CHS 22 is a special, mineral-based hydraulic fluid for use in specially marked containers for liquids, for hydraulic support of leveling, steering, & brake systems.

CARY CHS 22 was developed for vehicle hydraulics use in a temperature range between -40°C and 100°C.

Properties

- High viscosity index
- High pressure susceptibility
- Reliable wear protection
- Good oxidation stability
- Reliable protection against corrosion
- No foaming
- High ageing stability
- Low pour point

Effects

- Good flow flexibility at low temperatures
- High performance level
- Low freezing point
- Engine oil for all seasons

Suitable for/ we recommend this product for

DIN	51524 T3
ISO	7308
We recommend this product for:	
MB	343.0

Utilization

- Power steering gear
- Rear axle steering
- Level control system
- Active damping and engine support
- Hydrostatic drive for cooling fans, radiators, generators
- Shock absorber
- Central lock
- Electro hydraulic control of convertible tops

Special Notes:

- Attention: This product cannot be mixed with and is not compatible with brake fluids DOT 3, 4, 5 or 5.1. For Citroen vehicles please use the mineral-based LHM fluid for hydro pneumatic systems.

Disposal:

- **CARY CHS 22** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **CARY CHS 22** is fully compatible with comparable central hydraulic fluids and can be mixed trouble-free. However, it is recommended to refill only **CARY CHS 22**.

CARY CHS 22

Article No.	Packaging unit	
1222 042	Can	1 L