



COMCOR ATF-H

HC-Synthetic-Automatic-Transmission-Fluid

Description:

COMCOR ATF-H ATF-Dexron III H automatic transmission fluid is a sophisticated ATF gear oil. Carefully selected mineral and HC-Synthetic base oils and modified additive and effective ingredient combinations make the quality of this ATF perfect.

It is a special transmission oil for use in modern, self-engaging vehicle transmissions.

COMCOR ATF-H overlaps the requirements of Dexron II D, Dexron III F, Dexron III G ATFs. Outstanding ageing and oxidation stability makes it **COMCOR ATF-H** suitable for lifetime applications (Note manufacturer's specifications).

Properties

- Extrem wear protection
- High thermo stability
- Optimum foaming behaviour
- Optimum matched friction behaviour
- High load capacity
- High oxidation stability
- Excellent viscosity-temperature behaviour
- Extreme low pour point
- Neutral towards metals and sealing materials

Effects

- Optimal operating reliability at extreme conditions
- Excellent cold flow qualities
- Best lubrication
- All-year operation
- Reduces kinds by universal property

Suitable for/ we recommend this product for

We recommend this product for:	
GENERAL-MOTORS-CORPORATION	Dexron III H, Dexron III G
ALLISON	C-4/TES-389
BMW	83 22 9 407 807, 83 22 9 407 858
CATERPILLAR	TO-2
FORD	MERCON
FORD	M2C138-CJ, 166-H
MAN	339 Typ L1/V1/V2/Z1/Z2
MB	236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10
VOITH	55.6335, 55.6336.3X Extended Drain (G1363)
VOLVO	97340, 97341, 1161521, 1161511
VW	G 052 162 (TL 52 162)
ZF	TE-ML 02F,04D,09A,09B,11B,14A/ B,17C

Utilization

- Passenger car automatic gear
- Passenger car gear box according service instructions
- Passenger car servo steering according service instructions
- Vehicle hydraulic plants according service instructions
- Fluid couplings on vehicles in accordance with manufacturer's specifications
- Hydrodynamic converters on vehicles in accordance with manufacturer's specifications
- Not suitable for use in DCT/DSG- or CVT-transmissions

Disposal:

- **COMCOR ATF-H** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **COMCOR ATF-H** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **COMCOR ATF-H** when refilling.

Data are subject to change.

Attention: Service instructions should be observed!

KL/GE/AU/-
07/2021

COMCOR ATF-H

Article No.	Packaging unit	
303 672	Can	1 L
303 675	Can	20 L
303 676	Drum	60 L
303 678	Drum	200 L
343 679	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	852
Viscosity at 40°C	mm ² /s	-
Viscosity at 100°C	mm ² /s	7,26
Viscosity index		176
Flash point COC	°C	-
Pourpoint	°C	-54
TBN	mgKOH/g	-
Colour		red

