

# Driver Antifreeze SF-X 12 Plus ready for use - 37°C

**Ready-for-use lifetime coolant (free of silicates) Colour: pink/violet**

## Description:

**Driver Antifreeze SF-X 12 Plus ready for use -37°C** is a ready-to-use, ethylene glycol-based permanent coolant for summer and winter use with antifreeze and anticorrosion properties (all-season use).

**Driver Antifreeze SF-X 12 Plus ready for use -37°C**, the advanced ready-to-use radiator protection and thermal transfer medium with high-quality anticorrosion additives for engine and cooling system meets the current requirements in the development of automotive engineering.

**Driver Antifreeze SF-X 12 Plus ready for use -37°C** is free of nitrites, amines, phosphates and silicates.

## Properties:

- Longer and outstanding corrosion protection
- Improved heat transfer
- Decreased right to compensation regarding repairs at the cooling system
- Suitable for mixed fleets, one product for cars, trucks and construction machinery
- Ecologically desirable because of longer working life
- Avoidance of foaming
- Compatibility with hose and sealing materials
- Compatibility with varnishes

## Application:

**Driver Antifreeze SF-X 12 Plus ready for use -37°C** is excellent for engines built from cast iron, aluminium or a combination of the two metals and can be used in aluminium or copper alloy cooling systems.

**Driver Antifreeze SF-X 12 Plus ready for use -37°C** is particularly recommended for light alloy engines in which particular protection of the aluminium is demanded at higher temperatures.

It is recommended that the coolant be renewed after 3-6 years, depending on engine type and manufacturer.

**Suitable for/ we recommend this product for:**

We recommend this product for:	
AFNOR	NF-R 15-601 Type 3
AS	2108
ASTM	D 3306 Type III
ASTM	D 4985
ASTON MARTIN	
AUDI, SEAT, SKODA	G 12
BS	6580 : 1992
CLAAS	
CHRYSLER	MS-9176
CUMMINS	CES 14603
CUNA	NC 956-16
CNH	MAT 3624
DAF	74002
DEUTZ	DQC CB-14
FORD	ESD M97B49-A
FORD	ESE M97B49-A
FORD	WSS-M97B44-D
FFV	Heft R443

Data are subject to change.

Attention: Service instructions should be observed!

DV/WINTER/-  
09/2016

GM	1899 M, US 6277 M
ISUZU	
JASO	M-325
JENBACHER	TA 1000-0201
JIS	K 2234
JOHN DEERE	JDM H5
KOMATSU	
KSM	2142
LEYLAND TRUCKS	LTS 22 AF 10
MACK	EC1 (A4.05.09.01)
MAN	324 SNF (when using with black coolant hoses, not for silicone coolant hoses - coloured blue)
MAN	B&W D 36 5600
MB	325.3
NATO	S 759
ÖNORM	V 5123
OPEL	GM QL130100
PORSCHE	
RENAULT	Type D
SAE	J 1034
SCANIA	TB 1451
UNE	26361-88/1
VOLVO	VCS
VW	TL 774-D (G12), TL 774-F (G12+)

#### Miscibility:

- **Driver Antifreeze SF-X 12 Plus ready for use -37°C** is miscible with most coolants on the basis of ethylene glycol. To avoid the formation of sludge it is recommended to use pure **Driver Antifreeze SF-X 12 Plus ready for use -37°C**.

#### Driver Antifreeze SF-X 12 Plus ready for use -37°C

Article No.	Packaging unit	
1410 272	Can	1 L
1410 273	Can	1500 ml
1410 274	Can	5 L
1410 275	Can	20 L
1410 276	Drum	60 L
1410 278	Drum	200 L
1410 279	PE-Container	1000 L