



WINTRON SPORT 2

Hightec-Multigrade-Motor Oil 15W40

Description:

WINTRON SPORT 2 is a new, ultra-modern and multi-functional multigrade engine oil for petrol and diesel engines in passenger cars and vans with and without turbochargers - also recommended for harsh operating conditions.

WINTRON SPORT 2 ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

Properties

- · Multigrade character
- High engine cleanliness
- Universally applied for all gasoline and diesel engines
- Best wear protection
- Excellent viscosity-temperature behaviour
- High safety potential, also at boundary lubrication conditions
- · Ageing and viscosity stability
- Excellent detergent- and dispersant characteristics
- Low volatilization tendency
- · High, stable viscosity index
- Optimal protection against corrosion, oxidation, wear and foaming

Effects

- All-year operation
- High operating reliability at extreme conditions
- Prevents black sludge formation
- Very good cold starting properties
- Suitable for extended oil change intervals

Suitable for/ we recommend this product for

SAE	15W-40				
API	SN/CF				
ACEA	A3/B4				
We recommend this product for:					
MB	229.1				
VW	501.01, 505.00				

Utilization

- Four-stroke petrol engines
- with turbo charging
- with multivalve technology
- · with catalyst technology
- passenger car and transporter diesel engines
- Suction diesel
- Turbo diesel
- · CDI- HDI- and TDI-motors
- Direct-injection
- with catalyst technology

Disposal:

• WINTRON SPORT 2 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• WINTRON SPORT 2 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take WINTRON SPORT 2 when refilling.

WINTRON SPOR	RT 2	
Article No.	Packaging unit	
309 722	Can	1 L
<mark>3</mark> 09 723	Can	4 L
309 724	Can	5 L
30 <mark>9</mark> 725	Can	20 L
309 <mark>72</mark> 6	Drum	60 L
309 728	Drum	200 L
349 729	PE-Container	1000 L

0		
Typical characteristics:		
Specific weight at 15°C	kg/m³	866
Dynamic viscosity at -25°C	mPa.s	-
Viscosity at 40°C	mm ² /s	94
Viscosity at 100°C	mm²/s	14,0
Viscosity index		157
Flash point COC	°C	-
Pourpoint	°C	-30
TBN	mgKOH/g	10,3

Data are subject to change.

KL/MO/PKW/Attention: Service instructions should be observed!

KL/MO/PKW/07/2021