

BOSTON SP2

Hightec-Multigrade-Motor Oil 15W40

Description:

BOSTON SP2 is a new, ultra-modern and multi-functional multigrade engine oil for petrol and diesel engines in passenger cars and vans with and without turbochargers - also recommended for harsh operating conditions.

BOSTON SP2 ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

Properties

- Multigrade character
- High engine cleanliness
- Universally applied for all gasoline and diesel engines
- Best wear protection
- Excellent viscosity-temperature behaviour
- High safety potential, also at boundary lubrication conditions
- Ageing and viscosity stability
- Excellent detergent- and dispersant characteristics
- Low volatilization tendency
- High, stable viscosity index
- Optimal protection against corrosion, oxidation, wear and foaming

Effects

- All-year operation
- High operating reliability at extreme conditions
- Prevents black sludge formation
- Very good cold starting properties
- Suitable for extended oil change intervals

Suitable for/ we recommend this product for

SAE	15W-40
API	SN/CF
ACEA	A3/B4
We recommend this product for:	
MB	229.1
VW	501.01, 505.00

Utilization

- Four-stroke petrol engines
- with turbo charging
- with multivalve technology
- with catalyst technology
- passenger car and transporter diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- Direct-injection
- with catalyst technology

Disposal:

- **BOSTON SP2** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **BOSTON SP2** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **BOSTON SP2** when refilling.

BOSTON SP2

Article No.	Packaging unit	
1209 722	Can	1 L
1209 723	Can	4 L
1209 724	Can	5 L
1209 725	Can	20 L
1209 726	Drum	60 L
1209 728	Drum	200 L
1249 729	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	866
Dynamic viscosity at -25°C	mPa.s	-
Viscosity at 40°C	mm ² /s	94
Viscosity at 100°C	mm ² /s	14,0
Viscosity index		157
Flash point COC	°C	-
Pourpoint	°C	-30
TBN	mgKOH/g	10,3

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-
07/2021