

# BOSTON SP2

**Hightec-Multigrade-Motor Oil 15W40**

## Description:

**BOSTON SP2** is a new, ultra-modern and multi-functional multigrade engine oil for petrol and diesel engines in passenger cars and vans with and without turbochargers - also recommended for harsh operating conditions.

**BOSTON SP2** ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

## Properties

- Multigrade character
- High engine cleanliness
- Universally applied for all gasoline and diesel engines
- Best wear protection
- Excellent viscosity-temperature behaviour
- High safety potential, also at boundary lubrication conditions
- Ageing and viscosity stability
- Excellent detergent- and dispersant characteristics
- Low volatilization tendency
- High, stable viscosity index
- Optimal protection against corrosion, oxidation, wear and foaming

## Effects

- All-year operation
- High operating reliability at extreme conditions
- Prevents black sludge formation
- Very good cold starting properties
- Suitable for extended oil change intervals

## Suitable for/ we recommend this product for

SAE	15W-40
API	SN/CF
ACEA	A3/B4
We recommend this product for:	
MB	229.1
VW	501.01, 505.00

## Utilization

- Four-stroke petrol engines
- with turbo charging
- with multivalve technology
- with catalyst technology
- passenger car and transporter diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- Direct-injection
- with catalyst technology

## Disposal:

- **BOSTON SP2** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **BOSTON SP2** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **BOSTON SP2** when refilling.

## BOSTON SP2

Article No.	Packaging unit	
1209 722	Can	1 L
1209 723	Can	4 L
1209 724	Can	5 L
1209 725	Can	20 L
1209 726	Drum	60 L
1209 728	Drum	200 L
1249 729	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m³	866
Dynamic viscosity at -25°C	mPa.s	-
Viscosity at 40°C	mm²/s	94
Viscosity at 100°C	mm²/s	14,0
Viscosity index		157
Flash point COC	°C	-
Pourpoint	°C	-30
TBN	mgKOH/g	10,3

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-  
07/2021