

CORONA XH3

Hightec-HC-Synthetic-Motor Oil 5W30

Description:

CORONA XH3 is a hightec synthetic lightrun motor oil especially developed for heavily stressed petrol and diesel car motors. **CORONA XH3** meets the manufacturers' high quality demands for cars. It is excellently applicable for long oil changing intervals and for motors with direct injection. Ideal for hard use at motorways and over short distances.

Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability

Effects

- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties - rapid supply of all points of lubrication
- Very good operating reliability
- Optimal engine cleanliness
- Lowest oil consumption
- High margin of performance and high product stability
- Extended oil change intervals
- Prevents black sludge formation
- All-year operation

Suitable for/ we recommend this product for

SAE	5W-30
API	SN/CF/EC
ACEA	A3/B4
We recommend this product for:	
BMW	Longlife-98
GM	LL-B-025
MB	229.3
PORSCHE	approved
VW	502.00, 505.00

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Direct-injection
- with CDI-technology
- with catalyst technology

Disposal:

- **CORONA XH3** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **CORONA XH3** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **CORONA XH3** it is recommendable to use only **CORONA XH3** when refilling.

CORONA XH3

Article No.	Packaging unit	
1200 362	Can	1 L
1200 363	Can	4 L
1200 364	Can	5 L
1200 365	Can	20 L
1200 366	Drum	60 L
1200 368	Drum	200 L
1240 369	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	850
Dynamic viscosity at -30°C	mPa.s	4420
Viscosity at 40°C	mm ² /s	63,8
Viscosity at 100°C	mm ² /s	10,9
Viscosity index		171
Flash point COC	°C	230
Pourpoint	°C	-42
TBN	mgKOH/g	10,5

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-
02/2019