

PHOENIX D

Premium-Lightrun-Motor Oil 10W40

Description:

PHOENIX D is an highly alloyed lightrun diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines. To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss **PHOENIX D** lightrun engine contains full synthetic components meeting the demands of high tech.

Properties

- High wear protection
- Exceptional ageing and oxidation stability
- Excellent high temperature stability
- Very high lubrication stability
- Greatest possible engine cleanliness
- Low volatilization loss

Suitable for/ we recommend this product for

| SAE | 10W-40 | | | |
|--------------------------------|----------|--|--|--|
| API | CF/EC | | | |
| ACEA | B4 | | | |
| We recommend this product for: | | | | |
| MB | 229.1 | | | |
| PSA | B71 2296 | | | |
| RENAULT | RN0700 | | | |
| VW | 505.00 | | | |
| | | | | |

Effects

- Suitable for extended oil change intervals
- Optimal operating reliability
- Excellent cold starting properties rapid supply of all points of lubrication
- Prevents black sludge formation
- Fuel efficiency by lightrun properties
- All-year operation

Utilization

- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal:

PHOENIX D is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

PHOENIX D engine oil is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **PHOENIX D** when refilling.

| Packaging unit | |
|----------------|---------------------------|
| Can | 1 L |
| Can | 5 L |
| Can | 20 L |
| Drum | 60 L |
| Drum | 200 L |
| | |
| | |
| | Can Can Can Drum |

| Typical characteristics: | | |
|----------------------------|----------|------|
| | | |
| Specific weight at 15°C | kg/m³ | 856 |
| Dynamic viscosity at -25°C | mPa.s | 4240 |
| Viscosity at 40°C | mm^2/s | 95,4 |
| Viscosity at 100°C | mm^2/s | 15,0 |
| Viscosity index | | 166 |
| Flash point COC | °C | 232 |
| Pourpoint | °C | -39 |
| Sulphate ashes | % | - |
| TBN | mgKOH/g | 10,3 |

Data are subject to change.

DV/MO/PKW/-07/2021