

RENO 8STEP ATF

Special-High-Performance-HC-Synthetic-Automatic-Transmission-Fluid

Description:

Comcor ATF 8G is a modern high- performance ATF- automatic transmission fluid with a lowered viscosity based on the latest additive technology.

Due to the special composition with selected HC- synthetic oils and synthetic base oils (PAO), the special requirements of modern 6-, 8 and 9-step automatic transmissions are fulfilled in powerful sport utility vehicles (SUV) and vehicles of the upper middle sized class and the luxury class.

The high friction coefficient ensures a slip- free transmission of high torques.

Properties

- Adapted friction coefficient for sporty gear changes
- Prevents annoying friction vibrations
- Outstanding friction characteristics
- Excellent low temperature switching behavior
- Extrem wear protection
- Highest oxidation and aging stability
- Minimal foaming
- Neutral towards sealing materials

Effects

- Lowered viscosity for improved fuel efficiency
- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gearbox clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area

Suitable for/ we recommend this product for

We recommend this product for:	
BENTLEY	PY 112995PA
BMW	83 22 0 142 516
BMW	83 22 2 152 426
BMW	83 22 2 305 397
BMW	83 22 2 289 720
BMW	ATF 3+
CHRYSLER	68157995AA
FIAT	9.55550-AV5
HYUNDAI/KIA	040000C90SG
JAGUAR	02JDE 26444
JAGUAR/LAND ROVER	Fluid 8432
LAND ROVER	LR023288 / 232289
LAND ROVER	TYK 500050
MASERATI	231603
MOPAR	68157995AA
VW/AUDI/VAG	G 055 005 A1/A2/A6, G 055 162 A2/A6, G 055 540 A2, G 060 162 A1/A2/A6)
ZF	Lifeguardfluid 8 (S671 090 312)
ZF	Lifeguardfluid 6 (S671 090 255)
ZF	TE-ML 11 (6 HP + 8 HP)

Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

Disposal:

- **RENO 8STEP ATF** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **RENO 8STEP ATF** is only miscible with comparable lubrications and well tolerated. However, to get full advantage of **RENO 8STEP ATF** it is recommendable to use **RENO 8STEP ATF** when refilling.

Data are subject to change.

Attention: Service instructions should be observed!

DV/GE/AU/-
08/2021

RENO 8STEP ATF

Article No.	Packaging unit	
1203 612	Can	1 L
1203 615	Can	20 L
1203 616	Drum	60 L
1203 618	Drum	200 L
1243 619	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	841
Viscosity at 40°C	mm ² /s	29,3
Viscosity at 100°C	mm ² /s	5,5
Viscosity index		162
Flash point COC	°C	-
Pourpoint	°C	-48
Colour		Green

