

TULSA MAR 2T

Motor Oil for all 2-Stroke Outboard-Motors ashless for selfmixing and separate lubrication

Description:

TULSA MAR 2T is specially designed for all 2-stroke outboard engines developed ashless two-stroke oil that meets NMMA TC-W3.

Properties

- Excellent protection against rust and corrosion
- Can easily be mixed with gasoline
- High wear protection
- Extraordinary lubrication
- High oxidation stability
- Ash-free formula

Effects

- Optimal operating reliability
- Prevents against deposits - spark-plug bridge formation
- Environment-friendly - low smoke formation
- Selfmixing in tank
- Selfmixing and for separate lubrication

Suitable for/ we recommend this product for

NMMA (BIA)	TC-W3
------------	-------

Utilization

- All 2-stroke petrol outboard motors, jet skis, Personal Watercraft
- Typical mixture ratio of 1:50 - 2% (ideally lead-free) (Follow manufacturer's recommendation)

Disposal:

- TULSA MAR 2T is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- TULSA MAR 2T is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill TULSA MAR 2T only.

TULSA MAR 2T

Article No.	Packaging unit	
1205 122	Can	1 L
1205 124	Can	5 L
1205 125	Can	20 L
1205 126	Drum	60 L
1205 128	Drum	200 L
1245 129	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	876
Viscosity at 40°C	mm ² /s	35,6
Viscosity at 100°C	mm ² /s	6,29
Viscosity index		126
Flash point PM	°C	107
Pourpoint	°C	-30
TBN	mgKOH/g	8,7
Colour		brown

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/2T/-
07/2021