

TULSA MAR 2T

Motor Oil for all 2-Stroke Outboard-Motors ashless for selfmixing and separate lubrication

Description:

TULSA MAR 2T is specially designed for all 2-stroke outboard engines developed ashless two-stroke oil that meets NMMA TC-W3.

Properties

- Excellent protection against rust and corrosion
- Can easily be mixed with gasoline
- High wear protection
- Extraordinary lubrication
- High oxidation stability
- Ash-free formula

Effects

- Optimal operating reliability
- Prevents against deposits - spark-plug bridge formation
- Environment-friendly - low smoke formation
- Selfmixing in tank
- Selfmixing and for separate lubrication

Suitable for/ we recommend this product for

NMMA (BIA)	TC-W3
------------	-------

Utilization

- All 2-stroke petrol outboard motors, jet skis, Personal Watercraft
- Typical mixture ratio of 1:50 - 2% (ideally lead-free) (Follow manufacturer's recommendation)

Disposal:

- **TULSA MAR 2T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **TULSA MAR 2T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **TULSA MAR 2T** only.

TULSA MAR 2T

Article No.	Packaging unit	
1205 122	Can	1 L
1205 124	Can	5 L
1205 125	Can	20 L
1205 126	Drum	60 L
1205 128	Drum	200 L
1245 129	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m³	876
Viscosity at 40°C	mm²/s	35,6
Viscosity at 100°C	mm²/s	6,29
Viscosity index		126
Flash point PM	°C	107
Pourpoint	°C	-30
TBN	mgKOH/g	8,7
Colour		brown