

OIL-SOAK UP100

All-weather oil-bonding granulate Type III R

Description:

OIL-SOAK UP100 is a polyurethane-based foam, water repellent highly absorbent PU granulate for safe absorption of materials, oily chemicals and fuels.

The oil absorption capacity is hardly reduced by included water. By that it is even during rainy and wet conditions unchanged absorbent.

The absorption capacity of oil is ca. 24 ltr. per bag.

Highly absorbent, odor-binding, endless shelf life, protect the soil, water repellent.

Takes the oil and leaves the water.

The oil sucking capacity will not be reduced by soaked up water.

Grain size: 0.125 to 4 mm Type R III.

Primary Use: industry, commerce, roads, other traffic zones.

Dirt suitability: oily and greasy dirt

Product features: outdoor use

Key Industry: construction / road construction, chemical industry, printing industry, disposal companies, automotive / aircraft, fire department, handicraft, engineering, transport technology, logistics, warehousing.

Tests in use have shown further advantages::

- poor dust but with sufficient fineness to take oils also from gaps
- highly non-slipping, also at wetness
- highly step-safe, scarcely crumbling
- no causing of cratches at tiles and synthetic-coated grounds in workshops
- easy removal after usage
- fast, simple and inexpensive disposal

OIL-SOAK UP100

Article No.	Packaging unit	
1219 036	Sack	40 L

Data are subject to change.

Attention: Service instructions should be observed!

DV/SO/-
03/2017