



# COMCOR ATF 15 LV

Special-High-Performance-Automatic-Transmission-Fluid

## Description:

**COMCOR ATF 15 LV** is a modern high quality and high performance HC synthetic and PAO automatic transmission gear oil with a very low viscosity, especially designed for the new Mercedes Benz 7G- Tronic Plus automatic gear box (NAG2FE+). This automatic transmission oil strongly contributes to the reduce of fuel by it's very low viscosity.

## Properties

- Extrem wear protection
- Adapted friction characteristics
- Excellent low-temperature-switching behavior
- Anti-flatter stability, resistance to friction
- Highest oxidation stability
- Minimal foaming
- Neutral towards metals and sealing materials
- Excellent cooling performance

## Effects

- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gear clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area

## Suitable for/ we recommend this product for

We recommend this product for:

MB 236.15

## Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

## Disposal:

- **COMCOR ATF 15 LV** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **COMCOR ATF 15 LV** is only miscible with comparable lubrications and well tolerated. However, to get full advantage of **COMCOR ATF 15 LV** it is recommendable to use **COMCOR ATF 15 LV** when refilling.

## COMCOR ATF 15 LV

Article No.	Packaging unit	
303 582	Can	1 L
303 585	Can	20 L
303 586	Drum	60 L
303 588	Drum	200 L
343 589	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m³	846
Viscosity at 40°C	mm²/s	18,1
Viscosity at 100°C	mm²/s	4,4
Viscosity index		150
Flash point COC	°C	-
Pourpoint	°C	-51
Colour		darkblue

Data are subject to change.

Attention: Service instructions should be observed!

KL/GE/AU/-  
08/2021