

ONTARIO LLV

Fully-Synthetic-Ultra-High-Performance Fuel Economy Motoroil 0W-20

Description:

ONTARIO LLV is a fully synthetic ultra- high performance fuel economy engine oil for passenger cars´ gasoline and diesel engines with and without turbo chargers in passenger cars and transporters, especially out of the Volkswagen group.

ONTARIO LLV was especially designed to reduce fuel consumption and exhaust emission.

Additionally the CO² emission could be reduced significantly.

This engine oil is not backwards compatible with VW 504.00/ 507.00 or other VW specifications.

Properties

- Highest wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Significant wear reduction on the cylinder, camshaft, plain bearings and piston rings
- High oxidation and temperature stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

Effects

- Reduces fuel consumption at full and partial loading
- Excellent cold starting properties - rapid supply of all points of lubrication
- Reduction of CO² and exhaust emissions
- Optimal engine cleanliness
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

Suitable for/ we recommend this product for

SAE	0W-20
API	SN Plus
ACEA	C5
We recommend this product for:	
FORD	WSS-M2C 956-A1
PORSCHE	C20
VW	508.00, 509.00
VW	TL 52577

Utilization

- New VW four-stroke petrol engines with WIV systems
- with multivalve-technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- New VW passenger car diesel engines with WIV systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with CDi-technology
- with turbo charging
- with multivalve technology
- with catalyst technology
- This motor oil is not backward compatible.

Disposal:

- **ONTARIO LLV** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **ONTARIO LLV** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **ONTARIO LLV**, however, the use of **ONTARIO LLV** is worth recommending.

ONTARIO LLV

Article No.	Packaging unit	
1209 402	Can	1 L
1209 403	Can	4 L
1209 404	Can	5 L
1209 405	Can	20 L
1209 406	Drum	60 L
1209 408	Drum	200 L
1249 409	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	836
Dynamic viscosity at -35°C(CCS)	mPa.s	3980
Viscosity at 100°C	mm ² /s	8,1
Flash point COC	°C	234
Pourpoint	°C	-54
TBN	mgKOH/g	8,0

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/PKW/-
01/2024