

ONTARIO LLV

Fully-Synthetic-Ultra-High-Performance Fuel Economy Motoroil 0W-20

Description:

ONTARIO LLV is a fully synthetic ultra- high performance fuel economy engine oil for passenger cars' gasoline and diesel engines with and without turbo chargers in passenger cars and transporters, especially out of the Volkswagen group. **ONTARIO LLV** was especially designed to reduce fuel consumption and exhaust emission. Additionally the CO² emission could be reduced significantly.

This engine oil is not backwards compatible with VW 504.00/ 507.00 or other VW specifications.

Properties

- Highest wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Significant wear reduction on the cylinder, camshaft, plain bearings and piston rings
- High oxidation and temperature stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

Suitable for/ we recommend this product for

SAE	0W-20	
API	SN Plus	
ACEA	C5	
We recommend this	product for:	
FORD	WSS-M2C 956-A1	
PORSCHE	C20	
VW	508.00, 509.00	
VW	TL 52577	
		_

Effects

- Reduces fuel consumption at full and partial loading
- Excellent cold starting properties rapid supply of all points of lubrication
- Reduction of CO² and exhaust emissions
- Optimal engine cleanliness
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

Utilization

- New VW four-stroke petrol engines with WIV systems
- with multivalve-technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- New VW passenger car diesel engines with WIV systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with CDi-technology
- with turbo charging
- with multivalve technology
- with catalyst technology
- This motor oil is not backward compatible.

Disposal:

• **ONTARIO LLV** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• **ONTARIO LLV** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **ONTARIO LLV**, however, the use of **ONTARIO LLV** is worth recommending.

ONTARIO LLV			Typical characteristics:
Article No.	Packaging unit		Specific weight at 15°C kg/m ³ 836
1209 402	Can	1 L	Dynamic viscosity at - mPa.s 3980
1209 403	Can	4 L	35°C(CCS)
1209 404	Can	5 L	Viscosity at 100°C mm ² /s 8,1
1209 405	Can	20 L	Flash point COC°C234
1209 406	Drum	60 L	Pourpoint °C -54
1209 408	Drum	200 L	TBN mgKOH/g 8,0
1249 409	PE-Container	1000 L	

Data are subject to change. Attention: Service instructions should be observed!