

RENO 15LV ATF

Special-High-Performance-Automatic-Transmission-Fluid

Description:

RENO 15LV ATF is a modern high quality and high performance HC synthetic and PAO automatic transmission gear oil with a very low viscosity, especially designed for the new Mercedes Benz 7G- Tronic Plus automatic gear box (NAG2FE+). This automatic transmission oil strongly contributes to the reduce of fuel by it's very low viscosity.

Properties

- Extrem wear protection
- Adapted friction characteristics
- · Excellent low-temperature-switching behavior
- Anti-flatter stability, resistance to friction
- · Highest oxidation stability
- Minimal foaming
- · Neutral towards metals and sealing materials
- Excellent cooling performance

Suitable for/ we recommend this product for

We recommend	We recommend this product for:			
MB	236.15			

Effects

- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gear clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area

Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

Disposal:

RENO 15LV ATF is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• RENO 15LV ATF is only miscible with comparable lubrications and well tolerated. However, to get full advantage of RENO 15LV ATF it is recommendable to use RENO 15LV ATF when refilling.

RENO 15LV ATF		
Article No.	Packaging unit	
1203 582	Can	1 L
1203 585	Can	20 L
1203 586	Drum	60 L
1203 588	Drum	200 L
1243 589	PE-Container	1000 L

Typical characteristics:				
Specific weight at 15°C	kg/m³	846		
Viscosity at 40°C	mm²/s	18,1		
Viscosity at 100°C	mm²/s	4,4		
Viscosity index		150		
Flash point COC	°C	-		
Pourpoint	°C	-51		
Colour		darkblue		

Data are subject to change. Attention: Service instructions should be observed!