



THERA SUPERPLUS

Hightec-HC-Synthetic-Motor Oil 10W30

Description:

THERA SUPERPLUS is a high-performance, low-friction passenger car petrol and diesel engine oil of the latest generation. The use of high-quality HC-Synthetic components and high-quality mineral base oils, combined with the latest technology additives, **THERA SUPERPLUS** engine oil is excellently suited for use in modern car engines with and without turbochargers and for light commercial vehicles, even under harsh operating conditions.

THERA SUPERPLUS ensures reduced fuel and oil consumption thanks to its optimized formulation. Suitable for use the whole year round thanks to its viscosity range. Adding a special booster enhances the quality level to API SN, achieving improvements in stability against oxidation, protection against deposition, wear protection characteristics and low temperature behaviour. This ensures a cleaner engine and ultimately to a longer service life for it.

Properties

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Reduced oil consumption
- All-year operation

Suitable for/ we recommend this product for

SAE	10W-30
API	SN/CF/EC
ACEA	A3/B4
We recommend this product for:	
DAIHATSU	
HONDA	
HYUNDAI	
KIA	
LEXUS	
MAZDA	
MB	229.1
MITSUBISHI	
NISSAN	
SUBARU	
SUZUKI	
TOYOTA	
VW	505.00

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve-technology
- with turbo charging
- with catalyst technology
- Passenger car- and light commercial vehicle diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- with CDI-technology
- Direct-injection
- with catalyst technology

Disposal:

- **THERA SUPERPLUS** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **THERA SUPERPLUS** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **THERA SUPERPLUS** when refilling.

Data are subject to change.

Attention: Service instructions should be observed!

KL/MO/PKW/-
01/2022

THERA SUPERPLUS

Article No.	Packaging unit	
300 142	Can	1 L
300 143	Can	4 L
300 144	Can	5 L
300 145	Can	20 L
300 146	Drum	60 L
300 148	Drum	200 L
340 149	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	857
Dynamic viscosity at -25°C	mPa.s	3500
Viscosity at 40°C	mm ² /s	61,9
Viscosity at 100°C	mm ² /s	10,3
Viscosity index		154
Flash point COC	°C	232
Pourpoint	°C	-40
TBN	mgKOH/g	10,5

