

ARVADA ZH75 ECO

HC-Synthetic-Hypoid Gear Oil 75W

Description:

ARVADA ZH75 ECO is a HC-Synthetic high performance low friction transmission oil for manual transmissions with reduced cold viscosity for optimized transmission efficiency and cold starting. Used to lubricate synchronized and non-synchronized manual transmissions.

ARVADA ZH75 ECO brings due to the modern HC-Synthetic base an effective noise attenuation and remains extremely shear stable "Stay-in-grade" under all operating conditions.

This transmission oil was developed for various transmissions from car manufacturers such as Audi, BMW (Getrag), Mercedes-Benz, Mitsubishi, Nissan, Peugeot, Seat, Skoda, Volkswagen, Volvo.

Especially recommended for cars from BMW, Mercedes-Benz and VW.

Properties

- Excellent wear protection
- First-rate oxidation stability
- High shear stability
- Excellent viscosity-temperature behaviour
- Excellent cold viscosity for improved switchability
- High pressure susceptibility
- Excellent corrosion protection
- Prevents foaming
- Neutral towards metals and sealing materials

Effects

- Optimal operating properties
- Life-time suitably
- Lowered cold viscosity for excellent fuel efficiency
- Excellent cold flow characteristics
- Reduced fuel consumption and longer oil change intervals
- All-year operation

Suitable for/ we recommend this product for

SAE	75W
API	GL-4
We recommend this product for:	
BMW	MTF, LT-2/-3/-4
FIAT	MZ7
FORD	WSS-M2C200-D2
GM	1940764 / W16612
HONDA Special	MTF, MTF-II, MTF-III
MB	235.10
MITSUBISHI	MZ320065 Diaqueen SSTF-4
PSA	B 71 2316 (HBVFE), PSA 9730 A8
RENAULT	DC4 DW5 (6DCT 250 dry DCT9)
SPECIAL GEAR OIL	MTF 94
TRANSELF	TRT
VOLVO	97308, 97309
VW	G 052 527 A2, G 070 726 A2, G 052 178, G 052 512, G 052 726, G 060 726

Utilization

- Modern passenger car gear box

Disposal:

- **ARVADA ZH75 ECO** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **ARVADA ZH75 ECO** is fully tolerated with comparable lubrications and can be mixed. However, to get full advantage of **ARVADA ZH75 ECO** it is recommended not to mix **ARVADA ZH75 ECO** with other customary hypoid gear oils.

ARVADA ZH75 ECO

Article No.	Packaging unit	
1202 562	Can	1 L
1202 565	Can	20 L
1202 566	Drum	60 L
1202 568	Drum	200 L
1242 569	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	850
Viscosity at 40°C	mm ² /s	33,8
Viscosity at 100°C	mm ² /s	6,6
Viscosity index		156
Flash point COC	°C	215
Pourpoint	°C	-42

