



## Special-High-Performance-HC-Synthetic-Automatic-Transmission-Fluid

**COMCOR ATF 17 LV** is a high quality and modern high- performance HC- synthetic automatic transmission oil with a reduced viscosity, especially developed for use in the latest Mercedes- Benz 9-shift automatic transmissions (9G- Tronic/ NAG 3 model 725 011).

**Please follow manufacturer's instructions!**

## Effects

- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gearbox clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area
- Maximum fuel savings due to reduced viscosity

## Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

- **COMCOR ATF 17 LV** is assigned to category 2 of used oils and thus is free for disposal.

- **COMCOR ATF 17 LV** is only miscible with comparable lubrications and well tolerated. However, to get full advantage of **COMCOR ATF 17 LV** it is recommendable to use **COMCOR ATF 17 LV** when refilling.

KL/GE/AU/  
08/2021

Kuttenkeuler GmbH • D-50996 Köln • Fon +49 (0) 2236 / 96203-0 • Fax +49 (0) 2236 / 96203-27 + 61322  
email: [vertrieb.schmierstoffe@kuttenkeuler.com](mailto:vertrieb.schmierstoffe@kuttenkeuler.com) • [www.kuttenkeuler.com](http://www.kuttenkeuler.com)

**COMCOR ATF 17 LV**

Article No.	Packaging unit	
303 572	Can	1 L
303 575	Can	20 L
303 576	Drum	60 L
303 578	Drum	200 L
343 579	PE-Container	1000 L

**Typical characteristics:**

Specific weight at 15°C	kg/m <sup>3</sup>	850
Viscosity at 40°C	mm <sup>2</sup> /s	30,4
Viscosity at 100°C	mm <sup>2</sup> /s	6,2
Viscosity index		162
Flash point COC	°C	> 190
Pourpoint	°C	-45
Colour		Yellow-Brown

