

# RENO 17LV ATF

**Special-High-Performance-HC-Synthetic-Automatic-Transmission-Fluid**

## Description:

**RENO 17LV ATF** is a high quality and modern high- performance HC- synthetic automatic transmission oil with a reduced viscosity, especially developed for use in the latest Mercedes- Benz 9-shift automatic transmissions (9G- Tronic/ NAG 3 model 725 011).

This ATF gear oil is not backwards compatible. So it is not suitable for older gear boxes.

Please follow manufacturer´s instructions!

## Properties

- Extrem wear protection
- Adapted friction characteristics
- Excellent low temperature switching behavior
- Anti-flatter stability, resistance to friction
- Highest oxidation stability
- Minimal foaming
- Neutral towards metals and sealing materials
- Excellent cooling performance

## Suitable for/ we recommend this product for

| We recommend this product for: |   |
|--------------------------------|---|
| MB                             | 236.16, 236.17                                |
| MB                             | 236.41  |
| AISIN                          | AW F8FXX                                      |
| DSIH                           | 6p805 (Geely, Ssangyong, Mahindra,6sp)        |
| HYUNDAI                        | NWS-9638                                      |
| HYUNDAI/KIA                    | SP-IV, SPH-IV, SP-IV RR                       |
| JASO                           | 1-A-LV  |
| MITSUBISHI                     | ATF-J3, ATF-PA                                |
| MOPAR                          | 68218925AA                                    |
| NISSAN                         | MATIC S, MATIC W                              |
| SAAB                           | 93 165 147                                    |
| VOLVO                          | 6 speed MY 2011-2013 (P/N 31256774, 31256675) |
| VW                             | G 052 540, G 055 005, G 055 162               |
| ZF                             | 6 Speed (S671 090 255)                        |
| ZF                             | TE-ML 13                                      |

## Disposal:

- **RENO 17LV ATF** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **RENO 17LV ATF** is only miscible with comparable lubrications and well tolerated. However, to get full advantage of **RENO 17LV ATF** it is recommendable to use **RENO 17LV ATF** when refilling.

## Effects

- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gearbox clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area
- Maximum fuel savings due to reduced viscosity

## Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

**RENO 17LV ATF**

| <b>Article No.</b> | <b>Packaging unit</b> |        |
|--------------------|-----------------------|--------|
| 1203 572           | Can                   | 1 L    |
| 1203 575           | Can                   | 20 L   |
| 1203 576           | Drum                  | 60 L   |
| 1203 578           | Drum                  | 200 L  |
| 1243 579           | PE-Container          | 1000 L |

**Typical characteristics:**

|                         |                    |              |
|-------------------------|--------------------|--------------|
| Specific weight at 15°C | kg/m <sup>3</sup>  | 850          |
| Viscosity at 40°C       | mm <sup>2</sup> /s | 30,4         |
| Viscosity at 100°C      | mm <sup>2</sup> /s | 6,2          |
| Viscosity index         |                    | 162          |
| Flash point COC         | °C                 | > 190        |
| Pourpoint               | °C                 | -45          |
| Colour                  |                    | Yellow-Brown |

