



# FIVE TRONIC 1G2

Fully-Synthetic fuel saving smooth running engine oil SAE 5W-20

## Description:

**FIVE TRONIC 1G2** is a high performance motor oil which was especially developed for the most modern passenger cars petrol and diesel engines that are operated with low viscosity fuel- saving motor oils.

This motor oil is suitable for all types of vehicles for which this viscosity level is prescribed.

This viscosity level is recommended for many vehicles from Honda, Ford and other leading manufacturers.

## Properties

- Extrem wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss
- Very high cleaning capability
- Stable oil film at all operating temperatures

## Effects

- Reduces fuel consumption at full and partial loading
- Reduces emissions of particles and CO<sub>2</sub>, is good for the environment
- Excellent cold starting behaviour
- Very good operating reliability
- Optimal engine cleanliness
- Very low oil consumption
- High margin of performance and high product stability
- All-year operation

## Suitable for/ we recommend this product for

SAE	5W-20
API	SP (RC)
ILSAC	GF-6A
We recommend this product for:	
CHRYSLER	MS-6395
DAIHATSU	
FORD	WSS-M2C960-A
FORD	WSS-M2C945-B1
GM	Dexos 1 Gen 2
HONDA	
ISUZU	
KIA	
LEXUS	
MAZDA	
NISSAN	
SUBARU	
SUZUKI	
TOYOTA	

## Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with fuel injection
- with turbo charging
- with catalyst technology
- Hybrid vehicles
- Passenger car diesel engines
- with multivalve technology
- with turbo charging
- with CDi-technology
- with diesel particle systems(DPF)
- with catalyst technology

## Disposal:

- **FIVE TRONIC 1G2** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **FIVE TRONIC 1G2** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **FIVE TRONIC 1G2**, however, the use of **FIVE TRONIC 1G2** is worth recommending.

**FIVE TRONIC 1G2**

Article No.	Packaging unit	
309 432	Can	1 L
309 434	Can	5 L
309 435	Can	20 L
309 436	Drum	60 L
309 438	Drum	200 L
349 439	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	852
Dynamic viscosity at -30°C	mPa.s	4750
Viscosity at 40°C	mm <sup>2</sup> /s	47,5
Viscosity at 100°C	mm <sup>2</sup> /s	8,5
Viscosity index		157
Flash point COC	°C	230
Pourpoint	°C	-45
TBN	mgKOH/g	7,4

